



Effective Date - July 14, 2008

PRICE LIST

Magnetic Sensors Cordsets Brackets

Note: Sensors cannot be returned to factory for replacement unless the sensor is in the originally sealed factory package.

Magnetic Sensors					
Prewired 9 ft. Part No.	Quick Disconnect Part No.*	Electrical Characteristics	Wire Leads	Sensor Type	Application
9B49-000-031.....\$33.40	9B49-000-331.....\$43.60	Sourcing, PNP, 6-24 VDC, 0.2 Amp Max, 1.0 Voltage Drop	3	Electronic (LED)	4 mm Round Sensors for 1/2" Bore Pancake
9B49-000-032.....33.40	9B49-000-332..... 43.60	Sinking, NPN, 6-24 VDC, 0.2 Amp Max, 1.0 Voltage Drop	3	Electronic (LED)	
9C49-000-002.....19.30	9C49-000-302.....25.70	5-120V AC/DC, 0.04 Amp Max, 4 Watts Max, 2.5 Volt. Drop	3	Reed (LED)	4mm Round Sensors for New Global Series, GB Slides, Stopper Cylinders, and Swing Clamps
9C49-000-031.....27.30	9C49-000-331.....31.65	Sourcing PNP 6-30 VDC, 0.2 Amp Max, 6 Watts Max, 1.5 Voltage Drop	3	Electronic (LED)	
9C49-000-032.....27.30	9C49-000-332.....31.65	Sinking NPN 6-30 VDC, 0.2 Amp Max, 6 Watts Max, 1.5 Voltage Drop	3	Electronic (LED)	
949-000-00118.05	949-000-30125.65	0-120 VDC/VAC, 0.5 Amp Max, 5 Watt Max, 0 Voltage Drop	2	Reed (No LED)	1/4" Dovetail Sensors for New Global Series
949-000-00218.85	949-000-30226.30	5-120 VDC/VAC, 0.03 Amp Max, 4 Watt Max, 2.0 Voltage	2	Reed (LED)	
949-000-03123.80	949-000-33131.30	Sourcing PNP 6-24 VDC, 0.2 Amp Max, 0.5 Voltage Drop	3	Electronic (LED)	1/4" Dovetail Sensors for Pancake, Square1, Pancake II and New Global Series
949-000-03223.80	949-000-33231.30	Sinking NPN 6-24 VDC, 0.2 Amp Max, 0.5 Voltage Drop	3	Electronic (LED)	
949-200-00120.15	949-200-30127.70	0-120 VDC/VAC, 0.5 Amp Max, 5 Watt Max, 0 Voltage Drop	2	Reed (No LED)	1/4" Dovetail Sensors with adapter for 3/8" Dovetail Global Series and Global 32mm Stopper Cylinders
949-200-00220.90	949-200-30228.95	5-120 VDC/VAC, 0.03 Amp Max, 4 Watt Max, 2.0 Volt. Drop	2	Reed (LED)	
949-200-03125.95	949-200-33133.45	Sourcing PNP 6-24 VDC, 0.2 Amp Max, 0.5 Voltage Drop	3	Electronic (LED)	
949-200-03225.95	949-200-33233.45	Sinking NPN 6-24 VDC, 0.2 Amp Max, 0.5 Voltage Drop	3	Electronic (LED)	
9-2A197-1003.....29.90	9-2A197-1303.....38.50	5-120 VDC/VAC, 0.5 Amp Max, 10 Watt Max, SPST N.O. 3.5 Voltage Drop	2	Reed Switch	Band Clamp required for F Series Cylinders, EG, L and S Series Slides
9-2A197-1031.....32.05	9-2A197-1331..... 41.10	Sourcing, PNP, 6 - 24 VDC, 0.5 Amp Max, 1.0 Voltage Drop	3	Electronic	
9-2A197-1032.....32.05	9-2A197-1332..... 41.10	Sinking, NPN, 6 - 24 VDC 0.5 Amp Max, 1.0 Voltage Drop	3	Electronic	
9-2A197-1004.....25.80	9-2A197-1304.....34.85	5-120 VDC/VAC, 0.5 Amp Max, 10 Watt Max, SPST N.O. 3.5 Voltage Drop	2	Reed Switch	Tie Rod Clamp required for 1-1/8 to 3" Bore HP & MP, NFPA Cylinders (1-1/2" to 4" bore), SE, EZ and TS Slides
9-2A197-1033.....32.05	9-2A197-1333..... 41.10	Sourcing, PNP, 6 - 24 VDC, 0.5 Amp Max, 1.0 Voltage Drop	3	Electronic	
9-2A197-1034.....32.05	9-2A197-1334..... 41.10	Sinking, NPN, 6 - 24 VDC 0.5 Amp Max, 1.0 Voltage Drop	3	Electronic	
749-000-00439.20	749-000-504 48.30	5-240 VDC/VAC, 1 Amp Max, 30 Watt Max, SPST N.O. 3.0 Voltage Drop	2	Tie Rod Reed Sw.	Tie Rods for 4" to 8" Bore HP, MP, NFPA Cylinders (5" to 6" bore), and Multi-Power Air Press
749-000-03152.55	749-000-53161.65	Sourcing, PNP, 6 - 24 VDC, 1.0 Amp Max, 0.5 Voltage Drop	3	Tie Rod Electronic	
749-000-03252.55	749-000-53261.65	Sinking, NPN, 6 - 24 VDC 1.0 Amp Max, 0.5 Voltage Drop	3	Tie Rod Electronic	
749-111-00439.20	749-111-504 48.30	5-240 VDC/VAC, 1 Amp Max, 30 Watt Max, SPST N.O. 3.0 Voltage Drop	2	Tie Rod Reed Sw.	Tie Rods for 10" to 12" Bore HP, MP Cylinders
749-111-03152.55	749-111-53161.65	Sourcing, PNP, 6 - 24 VDC, 1.0 Amp Max, 0.5 Voltage Drop	3	Tie Rod Electronic	
749-111-03252.55	749-111-53261.65	Sinking, NPN, 6 - 24 VDC 1.0 Amp Max, 0.5 Voltage Drop	3	Tie Rod Electronic	

* Note: Female cordsets are required for use and sold separately below.

Cordsets	
Part No.	Application
CFC-1M.....\$14.35	All Quick Disconnect Sensors Except 749 Series
CFC-2M..... 16.05	
CFC-5M.....20.30	
CFC-2M-12.....23.25	749 Series Quick Disconnect Sensors
CFC-5M-12.....28.40	

Brackets	
Part No.	Application
800-A00-000.....\$7.70	Band Clamp 9-2A197 - F Series Cylinders; EG, L and S Series Slides
800-200-0007.70	Tie Rod Clamp 9-2A197 1-1/8" to 3" Bore HP & MP Cylinders; 1-1/2" to 4" Bore NFPA Cylinders; SE, EZ and TS Series Slides
900-300-0008.15	Band Clamp Adapter for 1/4" Dovetail Sensors. F Series Cylinders
SC-1, SC-2,5.30	Tie Rod Adapters for 1/4" Dovetail Sensors. Pancake II Cylinders
SC-3, SC-55.30	
SC-7, SC-8,5.30	
900-F00-0005.30	Tie Rod adapters for 1/4" Dovetail Sensors, Square Pancake II Cylinders
900-G00-0005.30	
900-H00-0005.30	
ER-XXX2.95 plus 1.20/inch	Adhesive mount extrusion for 1/4" dovetail sensors